

OUNIBO Pneumatic Components

SC Series Standard Cylinder • Datasheet

Order Code: SC{Bore}x{Stroke}{Magnet}-{Mount}

Segment	Meaning	Values
SC	Series	Fixed
{Bore}	Bore (mm)	16 / 25 / 32 / 40
{Stroke}	Stroke (mm)	25 / 50 / 75 / 100
{Magnet}	Magnet	blank=None / S=Magnet
{Mount}	Mounting	FA=Front flange / LB=Foot / CB=Clevis

Specifications

Parameter	Values
Bore (mm)	16 / 25 / 32 / 40
Stroke (mm)	25 / 50 / 75 / 100
Magnet	None / S
Mounting	FA / LB / CB

Selection Rules

- R1 Bore 16: stroke limited to 25 / 50
- R2 Magnet S requires bore >= 25
- R3 Clevis CB requires stroke <= 75

Reference Dimensions

Model	Bore	Stroke	Overall (mm)	Body (mm)
SC16x25-FA	16	25	138	85
SC25x50S-FA	25	50	188	110
SC32x50S-LB	32	50	188	110
SC40x100S-LB	40	100	288	160

Note: This datasheet contains sample data (fictional series) for catalog software development only, not real product data.
Generated by: sample-data/tools/gen-images.ps1